Q SERIES ELECTRIC SOLENOID VALVE

Q24DH-8

Q24D$_2$H-8

Ordering Code

Q24 - D - H - 8

Series Code	Control	Structure	Port Size
Q Series 4/2 Way Pillar Type Pneumatic Change Valves	**D:** Single Electric Control **D$_2$:** Double Electric Control **Q:** Single pneumatic Control **Q$_2$:** Double pneumatic Control	Pillar Type	**6:** G1/8 (M10×1) **8:** G1/4 (M12×1.25) **10:** G3/8 (M16×1.5) **15:** G1/2 (M20×1.5)

Graphic Symbol

Q24HD-□

Q24HD$_2$-□



Specification

Parameter \ Order Code	Q24HD-6 Q24HD$_2$-6	Q24HQ-6 Q24HQ$_2$-6	Q24HD-8 Q24HD$_2$-8	Q24HQ-8 Q24HQ$_2$-8	Q24HD-10 Q24HD$_2$-10	Q24HQ-10 Q24HQ$_2$-10	Q24HD-15 Q24HD$_2$-15	Q24HQ-15 Q24HQ$_2$-15
Orifice Size (mm)	6		8		10		20	
Working Pressure (MPa)	0.2 ~ 0.8							
Turn-around Time (S)	0.1							
Ambient Temperature (℃)	-10 ~ 55							
Medium Temperature (℃)	0 ~ 55							
Power Voltage (V)	Electric Control AC: 220,110,36 DC: 48,24,12 Voltage hunting permission amounts to definite value +10%~-15% Gas to control does not have this parameter							
Life (Ten Thousand Times)	⩾150							